



GENERAL FEATURURES

- Max working pressure 50 bar (725 PSI)
- Inlet G1/2 (BSP) with brass swivel attachment
- Device for adjusting width of spraying cone, reversible for left-handed users
- Micro-Jet diffuser with air mixing for micro-atomization of liquid sprayed
- Locking button on opening of control lever
- Ergonomic grip in reinforced Nylon®
- Stainless steel cylinder
- Internal metallic parts in stainless steel and brass
- Ceramic nozzle Ø1.5 mm (Ø0.06 ")
- Gaskets in EPDM
- Weight 640 g (1.4 lb)

	DISEGNO	5062400C	INDICE MODIFICA	2	CLASSE TOLLERANZA EN-ISO 2768-vL
	DENOMINAZIONE	PISTOLA IRROR."HYDRA" UG.1,5		FIRMA	Bassi L.
				DATA	06/12/2023
				SCALA	1:1.5
<small>QUESTO E' UN DOCUMENTO RISERVATO DI PROPRIETA' DI ARAG srf, via Palladio 5/A 42048 RUBIERA (RE) ITALY. IL SUO CONTENUTO NON POTRA' ESSERE COMUNICATO A TERZI SENZA IL PERMESSO SCRITTO DEL PROPRIETARIO. THIS CONFIDENTIAL DOCUMENT IS EXCLUSIVE PROPERTY OF ARAG srf, via Palladio 5/A 42048 RUBIERA (RE) ITALY. ITS CONTENTS CANNOT BE DISCLOSED TO ANYONE WITHOUT WRITTEN PERMISSION OF THE OWNER.</small>					

REV.01