



550532 – 1-ABS

Designed for in-pan placement, the 1-ABS shallow pan pump offers next generation technology for air conditioner condensate removal. Includes a built-in, advanced non-mercury mechanical switch that automatically triggers operation when condensate in the pan or reservoir reaches a preset level. Then, automatic shutoff occurs when the condensate level drops. Low weight, compact size, high lift and quiet operation make the Little Giant line of ABS pumps perfect for in-pan condensate and other waste-water removal.

Item: 550532

Model: 1-ABS

Ratings

Frequency	50 Hz
Amps - Full Load	0.6 A
Full Load Watts	70 W
Volts	230 VAC
Cord Length	11 ft
Maximum Flow Rate - 60Hz	3.33 gpm / 200 gph
Shut-Off	10 ft
Max PSIG - 60Hz	4.3 PSI
Safety Switch	No

Liquid

Max Fluid Temperature	120 °F
-----------------------	--------

Materials of Construction

Pump Body Material	Plastic
Check Valve	No

Installation

Discharge Type	Threaded - MNPT
Discharge	0.25 "
Suction Type	Screened
Product Length	6.32 "
Product Width	6.09 "
Product Height	4.31 "

Product Weight	4.31 lb
Carton Length	7 "
Carton Width	5.63 "
Carton Height	5.75 "
Tubing Included	No

Other

Minimum Order Quantity	1
------------------------	---

Accessories / Repair Kits

- Volute 116375
- Impeller 116437
- Seal Ring 928007
- Screen 101376
- Float Replacement 950060
- Float Screen 950284
- CV-2 1/4" FNPT (6.35 mm) to 1/4" (6.35 mm) OD tubing 599061

Electrical Agency Approvals	cCSAus
-----------------------------	--------

Standard Warranty	12 Months
-------------------	-----------

Documents



[Warranty Terms](#)