



584604 – TE-5-MD-HC

Our TE-5-MD-HC Chemical Pump is designed for the circulation of highly-corrosive solutions. Featuring 1/8 horsepower motor, the TE-5-MD-HC comes in 115/230 Volts and features 1/2" MNPT Discharge, 29.3 ft. Shut Off Head, 6 ft Cord.

Item: 584604

Model: TE-5-MD-HC

Ratings

HP	1/8 hp
Frequency	50Hz/60Hz
Amps - Full Load	3 A
Full Load Watts	325 W
Volts	To Be Configured
Cord Length	6 ft
Maximum Flow Rate - 60Hz	20 gpm / 1200 gph
Minimum Flow Rate - 60Hz	0.03 gpm / 2 gph
Shut-Off	29.3 ft
Minimum Head - 60Hz	1 ft
Shut Off Height - 60Hz	29.3 ft
Max PSIG - 60Hz	12.7 PSI
Switch Type	Manual

Liquid

Max Fluid Temperature	200 °F
-----------------------	--------

Materials of Construction

Pump Body Material	Plastic
Discharge Head Material	Thermoplastic
Impeller Material	GF Polypropylene

Installation

Discharge Type	Threaded - MNPT
Suction Type	Threaded - FNPT
Product Length	11.27 "
Product Width	5.2 "

Product Height	7 "
Pump Length	11.27 " / 28.63 cm
Product Weight	15.8 lb
Product Weight w/ Pack	16.3 lb
Carton Length	13.13 "
Carton Width	6.63 "
Carton Height	7.75 "

Other

Minimum Order Quantity	1
Standard Warranty	12 Months

Documents



[Warranty Terms](#)