



554631 – VCMA-20ULS-PRO

Our VCMA-20ULS-PRO pump effectively delivers high-efficiency condensate removal from air conditioners, gas furnaces, and condensing boilers.

Item: 554631

Model: VCMA-20ULS-PRO

Ratings

HP	1/30 hp
Frequency	50Hz/60Hz
Amps - Full Load	1.5 A
Full Load Watts	75 W
Volts	230 VAC
Cord Length	6 ft
Maximum Flow Rate - 60Hz	1.33 gpm / 80 gph
Max PSIG	8.6 PSI
Max Flow Rate - 50Hz	1.33 gpm / 80 gph
Shut-Off	20 ft
Safety Switch	Yes

Liquid

Max Fluid Temperature	140 °F
-----------------------	--------

Materials of Construction

Pump Body Material	Plastic
Check Valve	Yes

Installation

Discharge	0.38 "
Product Length	10.2 "
Product Width	4.8 "
Product Height	6.5 "
Product Weight	5.5 lb
Product Weight w/ Pack	5 lb
⌒ Length	12.13 "

Carton Width	4.94 "
Carton Height	6.75 "
Tubing Included	No

Other

Minimum Order Quantity	1
------------------------	---

Accessories / Repair Kits	<ul style="list-style-type: none">• Tank 154390• Rubber Feet 925047• Check Valve 3/8" 154724• Tank Bracket 154483• T-20/25 One carton of 25 pieces of 20' (6.01m) length 3/8" (9.5 mm) ID VC tubing 599033• T-3/8 100' (640.1 m) of 3/8" (9.5 mm) ID x 1/2" (12.37 mm) OD clear tubing 599107• CV-X38 3/8" (9.5 mm) OD rigid plastic or copper tubing 599058• Anti-Sweat Sleeve 10000014026• Check Valve 1/4" OD 154725
---------------------------	---

Electrical Agency Approvals	CSA/UL
-----------------------------	--------

Standard Warranty	36 Months
-------------------	-----------

Documents



[Warranty Terms](#)