

LINING DRUM 780

Redesigned for Faster Setups, Longer Shots, & Smoother Jobs



Redesigned from the ground up, Picote's new Lining Drum 780 brings next-level speed, control, & versatility to CIPP lining.

Engineered for real-world job sites, this lightweight yet rugged drum move easily through tight spaces & challenging terrain.

With a 2 stage, fast-action door design, smart multi-port integration, ergonomic controls, high operating pressure, expanded liner capacity & CE certification, this is innovation you can rely on job after job.

USES AND BENEFITS

2 Stage Fast-Action Door Design:

- Fast, safe, & secure locking system.
- Oversized rectangular door for easier loading.
- Large sight window to clearly see inside without opening.

Compact, Lightweight & Mobile:

- Aluminum construction, lightweight yet durable.
- Large wheels are easy to roll, even when fully loaded.
- Good ground clearance for stairs and thresholds.
- Offset center of gravity for balanced accessories attachment.

Versatile Multi-Port:

- Allows integration of CCTV, Smart Heat Cable, or steaming.

Reversible Turning Wheel:

- Switchable to either side, foldable handle.

Friction Band System:

- Unlimited stepless nozzle positioning.
- Quick release from trolley.
- Supports 20kg (44 lbs) ahead of front wheels .5m (1.6').

Maximized Capacity & Capability:

- Removable side support baffles to fit more liner.
- High Operating Pressure of 1.7bar (25 PSI).
- Storz or Camlock nozzle connections.
- Straight inversion heads with 45°/90° adaptors = less parts/cost.
- CE certification.

Technical Specifications

Category	Drum Model / Specification
Pipe Range	DN50-225 (2-9")
Weight	71kg (156.5 lbs)
Dimensions WxLxH	624.5x917.5x1131mm 24.6x36.1x44.5"
Liner Capacity*	DN100 (4") = 101m (331')
Max Pressure	1.7bar (25 PSI)
Connection	6" Storz or Camlock
Curing	Ambient, Hot Water, or Steam

* Liner capacity is an estimate and is influenced by liner type, thickness, width, and drum loading. Estimates were based on dry liner and straight winding inside the inversion drum.

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Super Midi Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Lining Drum 780 Products & Parts	
Part Number	Description
2300000781	Inversion Drum 780 with 6" Storz
2300000782	Inversion Drum 780 with 6" Camlock
2300000781US	Inversion Drum 780 with 6" Storz, US
2300000782US	Inversion Drum 780 with 6" Camlock, US
Parts & Accessories	
2301100050	Inversion Head DN50/2" with 6" Storz Coupling
2301100070	Inversion Head DN70/3" with 6" Storz Coupling
2301100100	Inversion Head DN100/4" with 6" Storz Coupling
2301100150	Inversion Head DN150/6" with 6" Storz Coupling
2301100200	Inversion Head DN200/8" with 6" Storz Coupling
2301100001	Inversion Head Elbow 45° with two 6" Storz Couplings
2301100002	Inversion Head Elbow 90° with two 6" Storz Couplings
2301200050	Inversion Head DN50/2" with 6" Male Camlock Coupling
2301200070	Inversion Head DN70/3" with 6 Male Camlock Coupling
2301200100	Inversion Head DN100/4" with 6" Male Camlock Coupling
2301200150	Inversion Head DN150/6" with 6" Male Camlock Coupling
2301200200	Inversion Head DN200/8" with 6" Male Camlock Coupling
2301200001	Inversion Head Elbow 45° with two 6" Camlock Couplings
2301200002	Inversion Head Elbow 90° with two 6" Camlock Couplings